

# Air And Shop Hose

## Impact Tool Air

Designed for tough service station and shop air tool applications. It features an EPDM tube and cover with a four spiral polyester reinforcement that keeps the hose kink resistant and flexible in extreme temperatures. The cover is resistant to abrasion, weathering, and ozone. Available coupled with brass fittings or uncoupled on reels. Also available with an attractive advertising disk for retail sales. Rated at 250 psi working pressure.

**Application:** Air  
**Style:** Impact Tool  
**Grade:** N/A  
**Specification:** N/A  
**Branding:** Thermoid 3/8" Impact Tool Air Hose (UPC) Made In USA  
**Cover Color:** Red  
**Tube:** EPDM  
**Reinforcement:** Four Spiral Polyester  
**Cover:** EPDM  
**Temperature Resistance:** -40°F to +212°F (Not for Steam Use)



| Product Number  | Inside Diameter (In.) | Length (Ft.) | Description                                     | Standard Pack Qty. | Master Pack Qty. | Ship Ctn. Wt. (Lbs.) |
|---|-----------------------|--------------|---|--------------------|------------------|----------------------|
| RED EPDM IMPACT TOOL AIR HOSE, M&M COUPLED 1/4" NPT AND UNCOUPLED; 250 PSI WORKING PRESSURE |                       |              |   |                    |                  |                      |
| 538-25  | 3/8                   | 25           | Impact Tool Air Hose, Coupled                   | carton             | 1                | 6                    |
| 538-35  | 3/8                   | 35           | Impact Tool Air Hose, Coupled                   | carton             | 1                | 8                    |
| 538-50  | 3/8                   | 50           | Impact Tool Air Hose, Coupled                   | carton             | 1                | 10                   |
| 438-25 ■  | 3/8                   | 25           | Impact Tool Air Hose, Coupled/Ad Disk           | carton             | 1                | 6                    |
| 438-25SL ■  | 3/8                   | 25           | Impact Tool Air Hose, Coupled & Sleeved/Ad Disk | carton             | 1                | 6                    |
| 438-50 ■  | 3/8                   | 50           | Impact Tool Air Hose, Coupled/Ad Disk           | carton             | 1                | 10                   |
| 438-50SL ■  | 3/8                   | 50           | Impact Tool Air Hose, Coupled & Sleeved/Ad Disk | carton             | 1                | 10                   |
| 438-R3  | 3/8                   | 300*         | Impact Tool Air Hose, Uncoupled                 | reel               | 1                | 55                   |
| 438-R   | 3/8                   | 700*         | Impact Tool Air Hose, Uncoupled                 | reel               | 1                | 135                  |

\*Maximum 2-piece spool or reel. No piece less than 50 feet.

## Heavy Duty Impact Tool Air

Designed for tough service station and shop air tool applications. It features an EPDM tube and cover with a four spiral polyester reinforcement that keeps the hose kink resistant and flexible in extreme temperatures. The cover is resistant to abrasion, weathering, and ozone. Available coupled with brass fittings or uncoupled on reels. Rated at 250 psi working pressure.

**Application:** Air  
**Style:** Heavy Duty Impact Tool  
**Grade:** N/A  
**Specification:** N/A  
**Branding:** Thermoid 1/2" HD Impact Tool Air Hose (UPC) Made In USA  
**Cover Color:** Red  
**Tube:** EPDM  
**Reinforcement:** Four Spiral Polyester  
**Cover:** EPDM  
**Temperature Resistance:** -40°F to +212°F (Not for Steam Use)



| Product Number   | Inside Diameter (In.) | Length (Ft.) | Description                                | Standard Pack Qty. | Master Pack Qty. | Ship Ctn. Wt. (Lbs.) |
|--|-----------------------|--------------|--|--------------------|------------------|----------------------|
| RED EPDM HEAVY DUTY IMPACT TOOL AIR HOSE, M&M COUPLED 1/2" NPT AND UNCOUPLED; 250 PSI WORKING PRESSURE |                       |              |  |                    |                  |                      |
| 412-25   | 1/2                   | 25           | Heavy Duty Impact Tool Air Hose, Coupled   | carton             | 1                | 7                    |
| 412-50   | 1/2                   | 50           | Heavy Duty Impact Tool Air Hose, Coupled   | carton             | 1                | 14                   |
| 412-R  | 1/2                   | 700*         | Heavy Duty Impact Tool Air Hose, Uncoupled | reel               | 1                | 185                  |

\* Maximum 2-piece spool or reel. No piece less than 50 feet.

▲ = MTO, ■ = Retail Packaged Products