

Air And Shop Hose

Heavy Duty Air

A multi-purpose hose designed for tough general service air and water applications. It features an EPDM tube and cover with a four spiral polyester reinforcement that keeps the hose kink resistant and flexible in extreme temperatures. The cover is resistant to abrasion, weathering, and ozone. Rated at 200 to 300 psi working pressure.

Application: Air
Style: Heavy Duty Bulk Air
Grade: N/A
Specification: N/A
Branding: Thermoid Valuflex/GS Size ID (pressure) PSI W.P. Made In USA
Cover Color: Red
Tube: EPDM, Medium Oil Resistant
Reinforcement: Four Spiral Polyester
Cover: EPDM
Temperature Resistance: -40°F to +212°F (Not for Steam Use)



Product Number	Inside Diameter (In.)	Length (Ft.)	Description	Standard Pack Qty.	Master Pack Qty.	Ship Ctn. Wt. (Lbs.)
RED HEAVY DUTY AIR HOSE (Bulk Maximum Two Pieces)						
#93	1/2	700*	Heavy Duty Air Hose 7/8" OD, 300 PSI W.P.	reel	1	185
#95	3/4	700*	Heavy Duty Air Hose 1-3/16" OD, 300 PSI W.P.	reel	1	275
#97	1	700*	Heavy Duty Air Hose 1-7/16" OD, 200 PSI W.P.	reel	1	375

* Maximum 2-piece spool or reel. No piece less than 50 feet.

Flex-Loc™ Push-On Air

This high quality hose can be used by all industries. It has a Class A high oil resistant tube and cover that offers excellent resistance to oil and petroleum based products. It has excellent coupling retention. It holds the special fitting tightly and safely. With an easy push, the spiral hose design grips the fitting securely and maintains a constant internal holding action. The fitting will not give, even under full working pressure. Not recommended for unleaded gasoline.

Application: Air
Style: Flex-Loc Push-On Hose
Grade: N/A
Specification: N/A
Branding: Size 250# WP Flex-Loc Made In USA
Cover Color: Black, Blue, Gray, Green, Red, or Yellow
Tube: Nitrile, RMA Class A
Reinforcement: Spiral Polyester
Cover: Nitrile/PVC Blend, RMA Class A
Temperature Resistance: -20°F to +180°F



Product Number	Inside Diameter (In.)	Length (Ft.)	Description	Standard Pack Qty.	Master Pack Qty.	Ship Ctn. Wt. (Lbs.)
FLEX-LOC PUSH-ON HOSE - Class A Oil Resistant Tube & Cover (Specify Black, Blue, Gray, Green, Red, or Yellow Cover); 250 PSI W.P.						
04398	1/4	250*	Flex-Loc Push-On Hose, Uncoupled	reel	1	23
06398	3/8	250*	Flex-Loc Push-On Hose, Uncoupled	reel	1	31
08398	1/2	250*	Flex-Loc Push-On Hose, Uncoupled	reel	1	39
10398	5/8	250*	Flex-Loc Push-On Hose, Uncoupled	reel	1	54
12398	3/4	250*	Flex-Loc Push-On Hose, Uncoupled	reel	1	62

* Maximum 2-piece spool or reel. No piece less than 50 feet.

▲ = MTO, ■ = Retail Packaged Products