

Fuel Line And PCV Hose



FI-Plus Fuel Injection

Designed for the extremely high temperatures generated by today's fuel injected engines. Temperature range of -29 to +275 degrees F (302 degrees F intermittent) with a burst pressure rating of 900 psi. This special hose handles E-85, diesel, bio-diesel and extended gasolines, resisting sour gas oxidation.

Application: Fuel Line
Style: Fuel Injection (SAE30R9)
Grade: N/A
Specification: SAE30R9
Branding: Size (mm) I.D. SAE30R9
 UPC KX Fuel Injection Hose
 Date Made In USA
Cover Color: Black
Tube: Fluoroelastomer
Reinforcement: Two Spiral Aramid Fiber
Cover: Synthetic Oil Resistant
Temperature Resistance: -29°F to +275°F
 (+302°F Intermittent)



Product Number	Inside Diameter (In.)	Length (Ft.)	Description	Standard Pack Qty.	Master Pack Qty.	Ship Ctn. Wt. (Lbs.)
FUEL INJECTION HOSE SAE30R9; 275°F Operating Temp.						
FI-502	1/4	10	Fuel Injection Hose; Coil	carton	1	1
FI-5025	1/4	25	Fuel Injection Hose; Spool	carton	1	2.5
FI-502250	1/4	250*	Fuel Injection Hose; Spool	spool	1	25
FI-503	5/16	10	Fuel Injection Hose; Coil	carton	1	1.4
FI-5035	5/16	25	Fuel Injection Hose; Spool	carton	1	3.5
FI-503250	5/16	250*	Fuel Injection Hose; Spool	spool	1	35
FI-504	3/8	10	Fuel Injection Hose; Coil	carton	1	1.7
FI-5045	3/8	25	Fuel Injection Hose; Spool	carton	1	4
FI-504250	3/8	250*	Fuel Injection Hose; Spool	spool	1	42
PI-502 ■	1/4	18"	Fuel Injection Hose (Retail Package)	carton/master	12	2
PI-503 ■	5/16	18"	Fuel Injection Hose (Retail Package)	carton/master	12	3
PI-504 ■	3/8	18"	Fuel Injection Hose (Retail Package)	carton/master	12	3

*Maximum 3-piece spool or reel. No piece less than 25 feet.

Gas Tank Filler

Designed for connection between gas tank and filler neck on automotive vehicles. This special hose handles leaded, unleaded, alcohol-added, diesel, and most modern fuels. Resists heat, weathering, abrasion, and ozone.

Application: Fuel Line
Style: Gas Tank Filler
Grade: N/A
Specification: SAE30R7
Branding: P/N Size (mm) - Date Code - Made In USA
Cover Color: Black
Tube: NBR
Reinforcement: Spiral Polyester Cord
Cover: CR
Temperature Resistance: 257°F



Product Number	Inside Diameter (In.)	Length (Ft.)	Description	Standard Pack Qty.	Master Pack Qty.	Ship Ctn. Wt. (Lbs.)
GAS TANK FILLER HOSE (Bagged)						
P508	1-1/2	2	Gas Tank Filler Hose	carton	6	10
P510	2	2	Gas Tank Filler Hose	carton	6	12

▲ = MTO, ■ = Retail Packaged Products