

TRANSPORTER® ULTRA-CHEM™

Transporter Ultra-Chem hose has been engineered to be extremely flexible. This hose will handle 98% of all common industrial chemicals. Ultra-Chem is ideal for pressure, gravity flow and suction service. This hose has been rated at **full vacuum**. The green EPDM cover is abrasion and chemical resistant. This hose can also come with a black EPDM cover.

Note: Working pressures reflect a permanent type coupling such as swage or internally expanded. For banded type couplings, the working pressure should reflect 65% of the ratings listed. ⚠ See Chemical Hose Warnings, pages 29 and 148.



| |
|---|
| Resistance: |
| |
| Branding: |
| Thermoid HBD Industries Transporter Ultra-Chem XXX PSI WP Made In USA |

- Cover Color:** Green
- Oil Resistance:** High at 70°F, not rated at 140°F
- Construction:**
 - Tube:** UHMWPE backed with compatible rubber layer
 - Cover:** EPDM
 - Reinforcement:** Multiple synthetic textile cords and a dual wire helix(es).
- Temperature Range:** Maximum temperature limitation +180°F (82°C) for most chemicals
- Packaging:** 100 ft. maximum

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|--------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| Green | | | | | | | | | | | |
| 17709008002 | 1 | 25.40 | 1.47 | 36.75 | 2 | 250 | 1.72 | 4.00 | 101.60 | 0.53 | 0.79 |
| 17709009002 | 1-1/4 | 31.75 | 1.78 | 44.50 | 2 | 250 | 1.72 | 4.00 | 101.60 | 0.75 | 1.12 |
| 17709010002 | 1-1/2 | 38.10 | 2.08 | 52.00 | 2 | 250 | 1.72 | 4.00 | 101.60 | 0.96 | 1.43 |
| 17709012002 | 2 | 50.80 | 2.58 | 64.50 | 2 | 250 | 1.72 | 6.00 | 152.40 | 1.30 | 1.93 |
| 17709013002 | 2-1/2 | 63.50 | 3.13 | 78.25 | 2 | 200 | 1.38 | 8.00 | 203.20 | 1.77 | 2.63 |
| 17709014002 | 3 | 76.20 | 3.66 | 91.50 | 2 | 200 | 1.38 | 9.00 | 228.60 | 2.09 | 3.11 |
| 17709016002 | 4 | 101.60 | 4.70 | 117.50 | 2 | 150 | 1.03 | 12.00 | 304.80 | 2.92 | 4.35 |
| 17709018002▲ | 6 | 152.40 | 6.90 | 172.50 | 4 | 150 | 1.03 | 30.00 | 762.00 | 5.77 | 8.59 |
| Black | | | | | | | | | | | |
| 17709300002 | 1 | 25.40 | 1.47 | 36.75 | 2 | 250 | 1.72 | 4.00 | 101.60 | 0.52 | 0.77 |

▲ = Make To Order (MTO)

Product information is subject to change. For full details, visit our website or contact Customer Service.

ATLAS™ ACID DISCHARGE

This is to be used as a discharge hose only. For pinch valve service or for use where acid forms crust inside hose that must be broken off. Also for handling many inorganic acids with the exception of strong oxidizing agents such as nitric, chromic and concentrated sulphuric. This hose will withstand most inorganic salts and alkalis. The black SBR/EPDM cover resists abrasion, sunlight and weathering.

⚠ See Chemical Hose Warnings, pages 29 and 148.



Cover Color: Black
Oil Resistance: Limited
Construction:
Tube: 3/16" NR
Cover: SBR/EPDM
Reinforcement: Multiple plies of strong, square-woven duck
Temperature Range: -40°F to +160°F
 -40°C to +71°C

Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.

Packaging: 50 ft. lengths
Minimum Run: 500 ft./size

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|-------|--------------|-------|-------|------------------|-------|------------------|------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 21204420502 | 3/4 | 19.05 | 1.50 | 38.10 | 4 | 150 | 1.03 | n/a | n/a | 0.70 | 1.04 |
| 21204421502 | 1 | 25.40 | 1.75 | 44.45 | 4 | 150 | 1.03 | n/a | n/a | 0.80 | 1.19 |
| 21204422502 | 1-1/4 | 31.75 | 2.00 | 50.80 | 4 | 150 | 1.03 | n/a | n/a | 0.90 | 1.34 |
| 21204423502 | 1-1/2 | 38.10 | 2.25 | 57.15 | 4 | 100 | 0.69 | n/a | n/a | 1.10 | 1.64 |
| 21204424502 | 2 | 50.80 | 2.81 | 71.44 | 4 | 100 | 0.69 | n/a | n/a | 1.40 | 2.08 |
| 21204425502 | 2-1/2 | 63.50 | 3.31 | 84.14 | 4 | 75 | 0.52 | n/a | n/a | 1.70 | 2.53 |
| 21204426502 | 3 | 76.20 | 3.81 | 96.84 | 4 | 75 | 0.52 | n/a | n/a | 1.90 | 2.83 |

n/a = Not Applicable

ATLAS™ ACID SUCTION & DISCHARGE

This hose is used for suction and discharge service handling many inorganic acids, except the strong oxidizing agents. This hose also withstands most salts and alkalis. This hose is made with capped, straight or enlarged ends. Can be made with Flexlock™ or Flexseal™ ends, so that no metal contacts corrosives. The black SBR/EPDM cover resists abrasion, sunlight and weather. The helical wire and multiple plies of reinforcement enable this hose to maintain full vacuum and be able to handle the discharge pressures. Flexible construction keeps the hose round when bent, reducing kinking. Tube thickness can be specified according to the severity of the service.

⚠ See Chemical Hose Warnings, pages 29 and 148.



Cover Color: Black
Oil Resistance: Limited
Construction:
Tube: 3/16" NR
Cover: SBR/EPDM
Reinforcement: Multiple plies of strong, square-woven duck with helical wire
Temperature Range: -40°F to +160°F
 -40°C to +71°C

Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.

Packaging: 50 ft. lengths maximum
Minimum Run: Varies with size. Contact customer service for required minimums


| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|---------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 21204482502▲ | 2 | 50.80 | 2.88 | 73.03 | 3 | 100 | 0.69 | 7.00 | 177.80 | 2.00 | 2.98 |
| 21204484502▲ | 2-1/2 | 63.50 | 3.50 | 88.90 | 3 | 75 | 0.52 | 8.00 | 203.20 | 2.60 | 3.87 |
| 21204486502▲ | 3 | 76.20 | 4.00 | 84.14 | 3 | 75 | 0.52 | 9.00 | 228.60 | 3.00 | 4.46 |
| 11404532502▲ | 3-1/2 | 88.90 | 4.50 | 114.30 | 3 | 75 | 0.52 | 12.00 | 304.80 | 3.40 | 5.06 |
| 11404534502▲ | 4 | 101.60 | 5.16 | 127.00 | 4 | 75 | 0.52 | 16.00 | 406.40 | 4.20 | 6.25 |
| 11404536502▲ | 4-1/2 | 114.30 | 5.56 | 141.29 | 4 | 75 | 0.52 | 18.00 | 457.20 | 5.20 | 7.74 |
| 11404538502▲ | 5 | 127.00 | 6.13 | 155.58 | 4 | 50 | 0.34 | 25.00 | 635.00 | 5.70 | 8.48 |
| 11404541502▲ | 6 | 152.40 | 7.13 | 180.98 | 4 | 50 | 0.34 | 30.00 | 762.00 | 6.90 | 10.27 |
| 11404543502▲ | 6-5/8 | 168.28 | 7.94 | 198.44 | 5 | 50 | 0.34 | 39.75 | 1009.65 | 8.00 | 11.91 |
| 11404546502▲ | 8 | 203.20 | 9.31 | 236.54 | 5 | 50 | 0.34 | 48.00 | 1219.20 | 11.40 | 16.97 |
| 11404548502▲ | 8-5/8 | 219.08 | 9.94 | 252.41 | 5 | 50 | 0.34 | 51.75 | 1314.45 | 12.40 | 18.45 |
| 11404550502▲ | 10 | 254.00 | 11.38 | 288.93 | 6 | 50 | 0.34 | 60.00 | 1524.00 | 14.10 | 20.98 |

▲ = Make To Order (MTO)

COMMANDER® ACID DISCHARGE

This is to be used as a discharge hose only. This hose handles many highly corrosive acids such as sulphuric acid, chromic acid, nitric acid, sodium dichromate, sodium hydrochlorite and glacial acetic acid. Good for use where acid slurry deposits on hose. The CR rubber cover resists abrasion, sunlight, weathering and scuffing.

▲ See Chemical Hose Warnings, pages 29 and 148.



| |
|---|
| Resistance: |
| |
| Branding: |
| Thermoid HBD Industries Commander Acid Discharge Hose Hypalon Tube Made In USA |

Cover Color: Black
Oil Resistance: Medium
Construction:
Tube: 3/16" CSM compound
Cover: CR
Reinforcement: Multiple plies of strong, square-woven duck
Temperature Range: -40°F to +160°F
 -40°C to +71°C

Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.

Packaging: 50 ft. lengths
Minimum Run: 500 ft./size


| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|-------|--------------|-------|-------|------------------|-------|------------------|------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 21204435502▲ | 1/2 | 12.70 | 1.25 | 31.75 | 4 | 150 | 1.03 | n/a | n/a | 0.50 | 0.74 |
| 21204436502▲ | 3/4 | 19.05 | 1.50 | 38.10 | 4 | 150 | 1.03 | n/a | n/a | 0.60 | 0.89 |
| 21204437502▲ | 1 | 25.40 | 1.75 | 44.45 | 4 | 150 | 1.03 | n/a | n/a | 0.80 | 1.19 |
| 21204438502▲ | 1-1/4 | 31.75 | 2.00 | 50.80 | 4 | 150 | 1.03 | n/a | n/a | 0.90 | 1.34 |
| 21204439502▲ | 1-1/2 | 38.10 | 2.25 | 57.15 | 4 | 100 | 0.69 | n/a | n/a | 1.00 | 1.49 |
| 21204440502▲ | 2 | 50.80 | 2.81 | 71.44 | 4 | 100 | 0.69 | n/a | n/a | 1.40 | 2.08 |
| 21204441502▲ | 2-1/2 | 63.50 | 3.31 | 84.14 | 4 | 75 | 0.52 | n/a | n/a | 1.70 | 2.53 |
| 21204442502▲ | 3 | 76.20 | 3.81 | 96.84 | 4 | 75 | 0.52 | n/a | n/a | 2.00 | 2.98 |

▲ = Make To Order (MTO)
 n/a = Not Applicable

COMMANDER® ACID SUCTION & DISCHARGE

This hose is used for suction and discharge in handling many highly corrosive acids and other materials such as sulphuric acid, chromic acid, nitric acid, sodium dichromate, sodium hypochlorite and glacial acetic acid. This hose can be assembled with Flexlock™ or Flexseal™ ends, so no metal contacts corrosives. The black CR cover resists abrasion, sunlight, weather and scuffing. Flexible construction keeps the hose round when bent, reducing kinking. The helical wire and multiple plies of reinforcement enable this hose to maintain full vacuum and be able to handle the discharge pressures. Tube thickness can be specified to meet various conditions used in an open, well-ventilated environment.

▲ See Chemical Hose Warnings, pages 29 and 148.



| |
|---|
| Resistance: |
| |
| Branding: |
| Thermoid HBD Industries Commander Acid Suction and Discharge Hose Hypalon Tube Made In USA |

Cover Color: Black
Oil Resistance: Medium
Construction:
Tube: 3/16" CSM compound
Cover: CR
Reinforcement: Multiple plies of strong, square-woven duck with helical wire
Temperature Range: -40°F to +160°F
 -40°C to +71°C

Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.

Packaging: 50 ft. lengths maximum
Minimum Run: Varies with size. Contact customer service for required minimums

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|---------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 21204462502▲ | 2 | 50.80 | 2.78 | 77.79 | 3 | 100 | 0.69 | 7.00 | 177.80 | 2.70 | 4.02 |
| 21204464502▲ | 2-1/2 | 63.50 | 3.50 | 88.90 | 3 | 75 | 0.52 | 8.00 | 203.20 | 3.20 | 4.76 |
| 21204466502▲ | 3 | 76.20 | 4.00 | 101.60 | 3 | 75 | 0.52 | 9.00 | 228.60 | 3.80 | 5.66 |
| 11404468502▲ | 3-1/2 | 88.90 | 4.50 | 114.30 | 3 | 75 | 0.52 | 12.00 | 304.80 | 4.20 | 6.25 |
| 11404470502▲ | 4 | 101.60 | 5.06 | 128.59 | 4 | 75 | 0.52 | 16.00 | 406.40 | 5.30 | 7.89 |
| 11404472502▲ | 4-1/2 | 114.30 | 5.69 | 144.46 | 4 | 75 | 0.52 | 18.00 | 457.20 | 6.40 | 9.52 |
| 11404474502▲ | 5 | 127.00 | 6.19 | 157.16 | 4 | 50 | 0.34 | 25.00 | 635.00 | 7.30 | 10.86 |
| 11404476502▲ | 6 | 152.40 | 7.19 | 182.56 | 4 | 50 | 0.34 | 30.00 | 762.00 | 8.50 | 12.65 |
| 11404478502▲ | 6-5/8 | 168.28 | 7.81 | 198.44 | 5 | 50 | 0.34 | 39.75 | 1009.65 | 9.80 | 14.58 |
| 11404480502▲ | 8 | 203.20 | 9.31 | 236.54 | 5 | 50 | 0.34 | 48.00 | 1219.20 | 13.30 | 19.79 |
| 11404482502▲ | 8-5/8 | 219.08 | 9.94 | 252.41 | 5 | 50 | 0.34 | 51.75 | 1314.45 | 15.00 | 22.32 |
| 11404485502▲ | 10 | 254.00 | 11.38 | 288.93 | 6 | 50 | 0.34 | 60.00 | 1524.00 | 17.00 | 25.30 |

▲ = Make To Order (MTO)

Product information is subject to change. For full details, visit our website or contact Customer Service.

TRANSPORTER® CHEMICAL B

Transporter Chemical B hose is a general purpose hose designed to handle strong and oxidizing acids, esters, ketones and alcohols. This hose features an EPDM cover that is resistant to heat, chemicals and weathering. This hose is rated at **full vacuum**. Chemical B hose also features a reinforcement of a spiral steel helix between synthetic textile plies.

▲ See Chemical Hose Warnings, pages 29 and 148.



Resistance:



Branding:

Thermoid HBD Industries
Transporter Chemical B WP
Made In USA

| | |
|---------------------------|---|
| Cover Color: | Brown |
| Oil Resistance: | Limited |
| Construction: | |
| Tube: | IIR |
| Cover: | EPDM |
| Reinforcement: | Spiral steel wire helix(es) between synthetic textile plies |
| Temperature Range: | -40°F to +200°F -40°C to +93°C |

Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.

| | |
|-------------------|--|
| Packaging: | 1" I.D. – 50 ft. 1-1/2" - 4" I.D. – 100 ft. |
|-------------------|--|

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|--------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 17704010002▲ | 1 | 25.40 | 1.50 | 38.10 | 2 | 150 | 1.03 | 3.00 | 76.20 | 0.65 | 0.97 |
| 17704015002▲ | 1-1/2 | 38.10 | 2.03 | 51.59 | 2 | 150 | 1.03 | 4.00 | 101.60 | 0.88 | 1.31 |
| 17704020002▲ | 2 | 50.80 | 2.56 | 65.09 | 2 | 150 | 1.03 | 6.00 | 152.40 | 1.23 | 1.83 |
| 17704030002▲ | 3 | 76.20 | 3.63 | 92.08 | 2 | 150 | 1.03 | 9.00 | 228.60 | 2.20 | 3.27 |
| 17704040002 | 4 | 101.60 | 4.69 | 119.06 | 2 | 100 | 0.69 | 12.00 | 304.80 | 3.00 | 4.46 |

▲ = Make To Order (MTO)

TRANSPORTER® CHEMICAL H

Transporter Chemical H hose is recommended to handle many inorganic acids, bases, alcohols, oils, fats, chemicals, greases and solvents. This hose features a CR cover that is weather, ozone and oil resistant. The tube compound is chemical, heat and abrasion resistant.

▲ See Chemical Hose Warnings, pages 29 and 148.



Resistance:



Branding:

HBD Industries Transporter
Chemical H WP
Made In USA

| | |
|---------------------------|---|
| Cover Color: | Yellow |
| Oil Resistance: | Medium |
| Construction: | |
| Tube: | CSM Black |
| Cover: | CR |
| Reinforcement: | Spiral steel wire helix(es) between synthetic textile plies |
| Temperature Range: | -40°F to +250°F -40°C to +121°C |

Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.

| | |
|-------------------|--|
| Packaging: | 100 ft. maximum Available in straight ends, uncapped only |
|-------------------|--|

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|--------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 17703010002▲ | 1 | 25.40 | 1.50 | 38.10 | 2 | 200 | 1.38 | 2.50 | 63.50 | 0.57 | 0.85 |
| 17703015002 | 1-1/2 | 38.10 | 2.00 | 50.80 | 2 | 150 | 1.03 | 4.50 | 114.30 | 0.83 | 1.24 |
| 17703020002 | 2 | 50.80 | 2.50 | 63.50 | 2 | 150 | 1.03 | 6.00 | 152.40 | 1.08 | 1.61 |
| 17703030002 | 3 | 76.20 | 3.56 | 90.49 | 2 | 150 | 1.03 | 9.00 | 228.60 | 1.81 | 2.69 |
| 17703040002▲ | 4 | 101.60 | 4.63 | 117.48 | 2 | 100 | 0.69 | 12.00 | 304.80 | 2.45 | 3.65 |

▲ = Make To Order (MTO)

TRANSPORTER® CHEMICAL V

Transporter Chemical V hose is capable of handling aromatic and aliphatic hydrocarbons and halo generated hydrocarbons. Chemical V hose will also handle animal oil, vegetable oil, and a wide range of chemicals. The NBR/PVC cover is both oil and abrasion resistant. The reinforcement of a spiral steel helix between synthetic textile plies enables this hose to be rated at **full vacuum**.

▲ See Chemical Hose Warnings, pages 29 and 148.



| |
|---|
| Resistance: |
|  |
| Branding: |
| HBD Industries Transporter Chemical V Made In USA |

Cover Color: Orange
Oil Resistance: Medium
Construction:
Tube: FKM, 1-1/2" and 2" I.D. – 1/8" thick
 3" I.D. and larger – 3/16" thick
 Exceeds RMA Class A
Cover: NBR/PVC
Reinforcement: Spiral steel wire helix(es) between synthetic textile plies
Temperature Range: -20°F to +250°F
 -29°C to +121°C
Consult the Chemical Resistance Guide for specific chemical/temperature recommendations.
Packaging: 100 ft. maximum
 Available in straight ends, uncapped only

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|--------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| 17701115002▲ | 1-1/2 | 38.10 | 2.06 | 52.39 | 2 | 150 | 1.03 | 4.00 | 101.60 | 1.20 | 1.79 |
| 17701120002▲ | 2 | 50.80 | 2.56 | 65.09 | 2 | 150 | 1.03 | 6.00 | 152.40 | 1.50 | 2.23 |
| 17701130002▲ | 3 | 76.20 | 3.69 | 93.66 | 2 | 150 | 1.03 | 9.00 | 228.60 | 2.40 | 3.57 |
| 17701140002▲ | 4 | 101.60 | 4.69 | 119.06 | 2 | 100 | 0.69 | 12.00 | 304.80 | 3.40 | 5.06 |

▲ = Make To Order (MTO)

TRANSPORTER® MULTI-CHEM®

Transporter Multi-Chem hose has been designed to be able to transfer chemicals and solvents. The XLPE tube is capable of resisting approximately 90% of all industrial chemicals. **Exceptions include elevated temperatures and strong oxidizing acids such as nitric acid and chromic. The maximum temperature rating for most chemicals is 150°F.** The green EPDM cover is abrasion and chemical resistant. This is a **full vacuum** hose.

Note: Working pressures reflect a permanent type coupling such as swage or internally expanded. For banded type couplings, the working pressure should reflect 65% of the ratings listed. ▲ See Chemical Hose Warnings, pages 29 and 148.



| |
|---|
| Resistance: |
|  |
| Branding: |
| Thermoid HBD Industries Transporter Multi-Chem Made In USA |

Cover Color: Green
Oil Resistance: High at 70°F, not rated at 140°F
Construction:
Tube: XLPE
Cover: EPDM
Reinforcement: Synthetic textile cords with wire helix(es)
Temperature Range: Maximum temperature limitation 150°F (66°C) for most chemicals
Packaging: 100 ft. maximum

| Product Number | Nominal I.D. | | Nominal O.D. | | Plies | Working Pressure | | Min. Bend Radius | | Weight | |
|----------------|--------------|--------|--------------|--------|-------|------------------|-------|------------------|--------|---------|--------|
| | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| Black | Green | | | | | | | | | | |
| N 17704600002▲ | 1 | 25.40 | 1.69 | 42.86 | 2 | 200 | 1.38 | 5.00 | 127.00 | 0.80 | 1.19 |
| N 17704601002▲ | 1-1/4 | 31.75 | 1.94 | 49.21 | 2 | 200 | 1.38 | 7.00 | 177.80 | 1.00 | 1.49 |
| N 17704602002▲ | 1-1/2 | 38.10 | 2.19 | 55.56 | 2 | 200 | 1.38 | 8.00 | 203.20 | 1.10 | 1.64 |
| N 17704603002 | 2 | 50.80 | 2.81 | 71.44 | 2 | 200 | 1.38 | 9.00 | 228.60 | 1.70 | 2.53 |
| N 17704608002▲ | 2-1/2 | 63.50 | 3.34 | 84.93 | 2 | 150 | 1.03 | 12.00 | 304.80 | 2.38 | 3.54 |
| N 17704604002▲ | 3 | 76.20 | 3.91 | 99.22 | 2 | 150 | 1.03 | 16.00 | 406.40 | 2.70 | 4.02 |
| N 17704605002▲ | 4 | 101.60 | 4.81 | 122.24 | 2 | 150 | 1.03 | 21.00 | 533.40 | 3.50 | 5.21 |

N = Non-Stock. All sizes available in black cover, contact Salisbury
 ▲ = Make To Order (MTO)