

Product information is subject to change. For full details, visit our website or contact Customer Service.

BOTTOM LOADING

Bottom Loading hose is engineered specifically for bottom loading, high pressure tank truck service. Construction of this hose has been stabilized to prevent elongation during service. This hose is rated at **full vacuum**. The black CR cover has excellent resistance to abrasion, weathering and ozone. The NBR tube is resistant to oil. Bottom Loading hose has a reinforcement of tire cord with a dual wire helix that allows this to handle a constant working pressure of 250 psi for both the 3" or 4" I.D.



Resistance:



Branding:

None

Cover Color:	Black
Oil Resistance:	High
Construction:	
Tube:	NBR with an aromatic range up to 55%
Cover:	CR
Reinforcement:	Tire cord with dual wire helix(es)
Temperature Range:	-20°F to +200°F -29°C to +93°C
Packaging:	100 ft. maximum. Minimum run of 1200 ft. per size.

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17811503002▲	3	76.20	3.75	95.25	4	250	1.72	12.00	304.80	2.30	3.42
17811504002▲	4	101.60	4.88	123.83	4	250	1.72	18.00	457.20	3.51	5.22

▲ = Make To Order (MTO)

COBRA™ FUEL OIL DELIVERY

Cobra Fuel Oil Delivery hose is designed for the delivery and transfer of fuels, oils, commercial gasoline, diesel, kerosene and related petroleum-based products for home delivery, marine, commercial and industrial service. It features an NBR/PVC cover with multiple spiral polyester reinforcement. This unique spiral construction adds strength and flexibility to the hose while making it easy to handle and kink resistant. The smooth, durable cover resists oil and abrasion and is less resistant to dragging, making it the driver's choice. This hose provides top performance and offers a constant working pressure of 250 psi in all sizes.

Note: A static wire is included on all sizes as a safety precaution

Reels (Thermocure)



Resistance:



Branding:

Thermoid Cobra I.D. Fuel Oil Hose
WP 250 PSI Made In USA
Month/Year

Cover Color:	Red
Oil Resistance:	High
Construction:	
Tube:	NBR, RMA Class A
Cover:	NBR/PVC, RMA Class A
Reinforcement:	High tensile spiral polyester cord
Temperature Range:	-40°F to +212°F -40°C to +100°C
Packaging:	Reels

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22564642662	1	25.40	1.50	38.10	4	250	1.72	7.00	177.80	0.47	0.70
22564802662	1-1/4	31.75	1.78	45.24	4	250	1.72	8.75	222.25	0.59	0.88
22564882662	1-3/8	34.93	1.88	47.63	4	250	1.72	9.25	234.95	0.65	0.97
22564962662	1-1/2	38.10	2.09	53.18	4	250	1.72	10.50	266.70	0.80	1.19

Cut and Coupled Lengths

Product Number Uncoupled	Product Number Coupled	Nominal I.D.		Lengths	
		(inches)	(mm)	(feet)	(meters)
22564642102	22564642111	1	25.40	100.00	30.48
22564642122	22564642131	1	25.40	125.00	38.10
22564642152	22564642141	1	25.40	150.00	45.72
22564642172	22564642171	1	25.40	175.00	53.34
22564802102	22564802111	1-1/4	31.75	100.00	30.48
22564802122	22564802131	1-1/4	31.75	125.00	38.10
22564802152	22564802141	1-1/4	31.75	150.00	45.72
22564802162	22564802171	1-1/4	31.75	175.00	53.34
22564882102	22564882111	1-3/8	34.93	100.00	30.48
22564882122	22564882131	1-3/8	34.93	125.00	38.10
22564882152	22564882141	1-3/8	34.93	150.00	45.72
22564882162	22564882201	1-3/8	34.93	175.00	53.34
22564962102	22564962111	1-1/2	38.10	100.00	30.48
22564962122	22564962131	1-1/2	38.10	125.00	38.10
22564962152	22564962141	1-1/2	38.10	150.00	45.72
22564962162	22564962171	1-1/2	38.10	175.00	53.34