

Product information is subject to change. For full details, visit our website or contact Customer Service.

## DARI-PREEN CREAMERY

Dari-Preen is designed for washdown service in creameries, dairies, packing houses, canneries and food processing plants. It features an EPDM tube and cover. Color coded white to indicate washdown service and cleanliness. Its tough cover resists scuffing and cracking. Dari-Preen handles hot water up to 200°F at 50 psi and it is rated for working pressures up to 250 psi on 1/2" I.D.



### Resistance:



### Branding:

Size WP Dari-Preen  
Made In USA

<b>Cover Color:</b>	White
<b>Oil Resistance:</b>	Limited
<b>Construction:</b>	
<b>Tube:</b>	EPDM
<b>Cover:</b>	EPDM
<b>Reinforcement:</b>	Spiral polyester yarn
<b>Temperature Range:</b>	-40°F to +180°F -40°C to +82°C
<b>Packaging:</b>	Reels, †50 ft. length – 1 per carton

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00544808400	1/2	12.70	0.91	23.02	4	250	1.72	3.00	76.20	0.29	0.43
00544812400	3/4	19.05	1.25	31.75	4	200	1.38	4.50	114.30	0.50	0.74
00544812450†	3/4	19.05	1.25	31.75	4	200	1.38	4.50	114.30	0.50	0.74

## SANI-WHITE™ WASHDOWN

Sani-White Washdown hose is recommended for open-end washdown service in food processing plants where service is not too severe, such as dairies, canneries, packing houses and bottling plants. This hose features a SBR tube that is heat resistant and stands up to the action of hot water and steam. It also resists saturated steam pressure to 40 psi (287°F) in open end service. Sani-White Washdown hose is available in tapered and straight ends. The white NBR/PVC cover resists oil, grease and cleaning compounds.



### Resistance:



### Branding:

Thermoid HBD Industries  
Sani-White Washdown  
Made In USA

<b>Cover Color:</b>	White
<b>Oil Resistance:</b>	Limited
<b>Construction:</b>	
<b>Tube:</b>	SBR
<b>Cover:</b>	NBR/PVC
<b>Reinforcement:</b>	Plies of strong fabric
<b>Temperature Range:</b>	-20°F to +160°F -29°C to +71°C
<b>Packaging:</b>	Tapered end – 50 ft. lengths Will not cut tapered ends Minimum run – 1200 ft. per size.

### Straight End

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
21284460502▲	1/2	12.70	0.94	23.81	3	150	1.03	n/a	n/a	0.25	0.37
21284461502	3/4	19.05	1.16	29.37	3	125	0.86	n/a	n/a	0.33	0.49
21284462502▲	1	25.40	1.47	37.31	4	100	0.69	n/a	n/a	0.46	0.68

▲ = Make To Order (MTO)

n/a = Not Applicable

### Tapered End

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
21284465502▲	3/4	19.05	1.16	29.37	3	125	0.86	n/a	n/a	0.33	0.49

▲ = Make To Order (MTO)

n/a = Not Applicable