

Product information is subject to change. For full details, visit our website or contact Customer Service.

## PUMPFLEX® II – Jumper

Pumpflex II - Jumper hose primary application is the dual low hose dispenser converted to Stage II vapor recovery external liquid line connection. This hose is used in conjunction with the Pumpflex II hose.

**Note: Do not use reusable couplings with this product.**



### Resistance:



### Branding:

Thermoid Size Pumpflex II  
Gasoline Hose UL Listed 97MO  
Made In USA Month/Year

<b>Cover Color:</b>	Black
<b>Oil Resistance:</b>	High, Medium-High
<b>Construction:</b>	
<b>Tube:</b>	NBR/PVC, RMA Class A
<b>Cover:</b>	Thermalon™, U/L approved, RMA Class B
<b>Reinforcement:</b>	1 wire braid (Hardwall)
<b>Temperature Range:</b>	-40°F to +180°F -40°C to +82°C
<b>Packaging:</b>	Bulk

### Coupled Lengths, Male x Swivel Permanent Fittings

Product Number	Nominal I.D.		Lengths		Weight per Length	
	(inches)	(mm)	(inches)	(mm)	(lbs)	(Kgs)
22341481271▲	3/4	19.05	14.00	355.60	1.42	0.64
22341481051▲	3/4	19.05	16.00	406.40	1.47	0.67
22341481561▲	3/4	19.05	18.00	457.20	1.56	0.71
22341481061▲	3/4	19.05	21.00	533.40	1.63	0.74
22341481571▲	3/4	19.05	24.00	609.60	1.72	0.78

▲ = Make To Order (MTO)

## PUMPFLEX® MARINA – Softwall

Pumpflex Marina hose is color coded green for marina use. This durable hose is designed to handle severe weather conditions, rough deck or dock use. It has a durable four spiral construction and static wire for continuity. This hose can be used for all types of gasoline, oil and other petroleum products. The green cover is oil and weather resistant as well as being UL approved.



### Resistance:



### Branding:

Thermoid Size Pumpflex Marina  
Hose UL Listed 97MO Made In  
USA Month/Year

<b>Cover Color:</b>	Green
<b>Oil Resistance:</b>	High, Medium-High
<b>Construction:</b>	
<b>Tube:</b>	NBR/PVC, RMA Class A
<b>Cover:</b>	CM, RMA Class B
<b>Reinforcement:</b>	Spiral polyester yarn with static wire (Softwall)
<b>Temperature Range:</b>	-40°F to +180°F -40°C to +82°C
<b>Packaging:</b>	Reels

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22463484662	3/4	19.05	1.13	28.58	4	200	1.38	4.50	114.30	0.32	0.48
22464644662	1	25.40	1.50	38.10	4	150	1.03	7.00	177.80	0.62	0.92