

Product information is subject to change. For full details, visit our website or contact Customer Service.

SUPERLITE® HI-FLO™ WHIP

Superlite Hi-Flo Whip hose's primary application is the "breakaway" connection from the pump to the primary hose assembly. This hose is used in conjunction with Superlite Hi-Flo Co-Ax assembly. **Note: Do not use reusable couplings with this product.**



Resistance:



Branding:

Manufacturer's Identification,
Product Name UL Listed

Cover Color: Black
Oil Resistance: High, Medium-High
Construction:
Tube: NBR/PVC
Outer Vapor Hose: Special lightweight helical synthetic polymer material
Cover: NBR/PVC
Reinforcement: Braided steel wire
Temperature Range: -40°F to +180°F
 -40°C to +82°C
Packaging: Individual carton, 10 per master carton
Coupling: Machined brass – built-in swivel nut

Superlite Hi-Flo Whip Product Number	Length	
	(inches)	(mm)
22314444041	10.00	254.00
22314444051	12.00	304.80

SUPERLITE® Q CO-AX® & SUPERLITE® QV (Venturi)

The inside working mechanisms of these Q hoses are the same as Superlite V and Superlite® Hi-Flo™ Co-Ax®. The Q difference is on the outside with the helical synthetic polymer material. The covers of both hoses will coordinate with any other hose on your dispenser unit. Both hoses are UL Listed and CARB and EPA approved.

Coupling: Machined brass – built-in swivel nut
 Aluminum ferrule with machined internal grooves viton O-ring.



Resistance:



Branding:

Manufacturer's Identification,
Product Name UL Listed

Cover Color: Black
Oil Resistance: High, Medium-High
Construction:
Tube: NBR/PVC, RMA Class A
Outer Vapor Hose: Special lightweight helical synthetic polymer material
Cover: NBR/PVC, RMA Class A
Reinforcement: Braided steel wire
Temperature Range: -40°F to +180°F
 -40°C to +82°C
Packaging: Individual carton, 6 per master carton
Retractor Clamp: Use product number 22972150021. Max. tension is 12 lbs.

Product Number	Nominal I.D.		Nominal O.D.		Steel Braid Reinforcement	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
Inner Hose	5/8	15.88	0.88	22.23	1	200	1.38	4.00	101.60	0.23	0.34
Outer Hose	1-3/8	34.93	1.63	41.28	1	25	0.17	4.00	101.60	0.12	0.18

Superlite Q Co-Ax Product Number w/o Venturi	Length	
	(feet)	(meters)
22985555041▲	4.00	1.22
22985555051▲	5.00	1.52
22985555061▲	7.00	2.13
22985555071▲	7.50	2.29
22985555081▲	8.00	2.44
22985555091	8.50	2.59
22985555101	9.00	2.74
22985555111	9.50	2.90
22985555121	10.00	3.05
22985555131	10.50	3.20
22985555141	11.00	3.35
22985555151	11.50	3.51
22985555161	12.00	3.66
22985555171	12.50	3.81

▲ = Make To Order (MTO)

Superlite QV Product Number w/ Venturi	Length	
	(feet)	(meters)
22986666041▲	4.00	1.22
22986666051▲	5.00	1.52
22986666061▲	7.00	2.13
22986666071	7.50	2.29
22986666081	8.00	2.44
22986666091	8.50	2.59
22986666101	9.00	2.74
22986666111	9.50	2.90
22986666121	10.00	3.05
22986666131	10.50	3.20
22986666141▲	11.00	3.35
22986666151▲	11.50	3.51
22986666161▲	12.00	3.66
22986666171▲	12.50	3.81

▲ = Make To Order (MTO)