

Product information is subject to change. For full details, visit our website or contact Customer Service.

TRANSPORTER® EBONITE™ LT CORRUGATED TANK TRUCK

The Transporter Ebonite LT Corrugated Tank Truck hose is designed to handle the applications for suction and discharge for tank truck, tank car and bulk station. This hose is used to convey gasoline, distilled kerosene, diesel and other fuels with maximum aromatic content of 30% to -65°F. This hose features a flat corrugated NBR cover which is ideal for those applications where flexibility and weight are issues. The two plies of polyester cord with a dual wire helix reinforcement allows this hose to be rated at **full vacuum**.



Resistance:



Branding:


Thermoid HBD Industries Inc.
Ebonite™ LT 150 PSI WP
Made In USA

Cover Color:	Black
Oil Resistance:	Medium-High
Construction:	
Tube:	NBR (low temperature)
Cover:	NBR/PVC corrugated
Reinforcement:	2 plies of polyester cord with a dual wire helix(es) between plies
Temperature Range:	-65°F to +180°F -54°C to +82°C
Packaging:	100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17813057002	1-1/2	38.10	2.06	52.39	2	150	1.03	3.00	76.20	0.90	1.34
17813058002	2	50.80	2.56	65.09	2	150	1.03	4.00	101.60	1.20	1.79
17813060002	3	76.20	3.56	90.49	2	150	1.03	5.50	139.70	1.80	2.68
17813065002	4	101.60	4.66	118.27	2	150	1.03	8.00	203.20	2.70	4.02

TRANSPORTER® L.W. CORRUGATED TANK TRUCK

The Transporter L.W. Corrugated Tank Truck hose is ideal for the transfer of gasoline or other petroleum-based products where a lightweight, extremely flexible hose is required. This hose is recommended for most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The NBR tube is oil resistant. This hose also features a NBR/PVC cover that is both oil and abrasion resistant. This is rated a **full vacuum** hose.



Resistance:



Branding:

Thermoid HBD Industries Inc.
Transporter LW Tank Truck
Made In USA

Cover Color:	Black
Oil Resistance:	High
Construction:	
Tube:	NBR, RMA Class A
Cover:	NBR/PVC – corrugated. Also available in orange
Reinforcement:	2 plies of polyester cord with a dual wire helix(es) between plies
Temperature Range:	-30°F to +200°F -34°C to +93°C
Packaging:	100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17814491002▲	2	50.80	2.56	65.09	2	100	0.69	5.00	127.00	1.00	1.49
17814493002▲	3	76.20	3.69	93.66	2	100	0.69	7.50	190.50	1.80	2.68
17814494002▲	4	101.60	4.69	119.06	2	100	0.69	9.00	228.60	2.50	3.72

* All sizes available in an orange cover, contact Salisbury for details
▲ = Make To Order (MTO)