

Product information is subject to change. For full details, visit our website or contact Customer Service.

## WD-150 WATER DISCHARGE

WD-150 is the heavy-duty water discharge hose suitable for construction sites, work boats and mines where abrasion resistance and higher working pressures are required. This hose features a reinforcement of two to four plies of polyester cord, depending on the I.D., that allows this hose to work at a constant working pressure of 150 psi regardless of hose I.D. The EPDM tube and cover offer excellent heat resistance.



<b>Cover Color:</b>	Black
<b>Oil Resistance:</b>	Limited
<b>Construction:</b>	
<b>Tube:</b>	EPDM
<b>Cover:</b>	EPDM
<b>Reinforcement:</b>	Heavy plies of polyester cord in sizes 1" to 4" I.D. – 2 plies 5" and 6" I.D. – 4 plies
<b>Temperature Range:</b>	-40°F to +180°F -40°C to +82°C
<b>Packaging:</b>	100 ft. maximum

Product Number	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17826010002▲	1	25.40	1.28	32.54	2	150	1.03	n/a	n/a	0.27	0.40
17826012502▲	1-1/4	31.75	1.53	38.89	2	150	1.03	n/a	n/a	0.32	0.48
17826015002▲	1-1/2	38.10	1.78	53.18	2	150	1.03	n/a	n/a	0.38	0.57
17826020002	2	50.80	2.28	57.94	2	150	1.03	n/a	n/a	0.56	0.83
17826025002	2-1/2	63.50	2.80	71.04	2	150	1.03	n/a	n/a	0.70	1.04
17826030002	3	76.20	3.28	83.34	2	150	1.03	n/a	n/a	0.76	1.13
17826040002	4	101.60	4.31	109.54	2	150	1.03	n/a	n/a	1.13	1.68
17826050002▲	5	127.00	5.50	139.70	4	150	1.03	n/a	n/a	2.45	3.65
17826060002▲	6	152.40	6.50	165.10	4	150	1.03	n/a	n/a	2.77	4.12

▲ = Make To Order (MTO)

n/a = Not Applicable