

Product information is subject to change. For full details, visit our website or contact Customer Service.

## ZEPHYR™ AIR

Zephyr is an industrial strength high-pressure, wire-braid air hose. It is well suited for multiple uses in air tool and air activated equipment. It has applications for use in either construction or industrial environments. Zephyr Air hose features a variety of hose construction designs, sizes and working pressures to fit your application. In the 1/2" I.D. to 1" I.D. sizes, Zephyr features a SBR/NBR tube. In 1-1/4" I.D. or larger sizes, Zephyr has an EPDM tube. All hose sizes are reinforced with heavy-duty, spiral wire braids to provide excellent strength and durability. Zephyr's cover consists of a NBR/PVC compound in the 1/2" I.D. to 1" I.D. sizes. EPDM is the cover compound for sizes 1-1/4" I.D. and larger. All hose sizes have a distinct yellow cover that is abrasion, kink and ozone resistant. Zephyr Air hose provides a dependable and constant working pressure. Zephyr has 3 different working pressure ranges to select from, including 500, 650 or 1000 psi. This durable, high-pressure air hose delivers smooth, trouble-free performance. It is available in sizes and lengths to fit your requirements.



### Resistance:



### Branding:

Thermoid Zephyr Air Hose WP  
Made In USA

<b>Cover Color:</b>	Yellow
<b>Oil Resistance:</b>	Determined by size
<b>Construction:</b>	
<b>Tube:</b>	SBR/NBR, RMA Class C: 1/2" to 1" EPDM, RMA Class C: 1-1/4" and over
<b>Cover:</b>	NBR/PVC, RMA Class A: 1/2" to 1" EPDM, RMA Class C: 1-1/4" and over
<b>Reinforcement:</b>	One or multiple wire braids
<b>Temperature Range:</b>	-40°F to +180°F -40°C to +82°C
<b>Packaging:</b>	50 ft. lengths – all sizes; Reels – 1/2" to 1"

Product Number	Nominal I.D.		Nominal O.D.		Braids	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22441328662▲	1/2	12.70	0.81	20.64	1	1000	6.89	3.00	76.20	0.32	0.48
22441488662▲	3/4	19.05	1.13	28.58	1	1000	6.89	4.50	114.30	0.44	0.65
22441648662▲	1	25.40	1.38	34.93	1	1000	6.89	7.00	177.80	0.77	1.15
01014444502▲	1-1/4	31.75	1.81	46.04	1	650	4.48	8.75	222.25	0.90	1.34
010144445502▲	1-1/2	38.10	2.00	50.80	1	500	3.45	10.50	266.70	1.00	1.49
010144446502▲	2	50.80	2.50	63.50	2	500	3.45	14.00	355.60	1.40	2.08
010144447502▲	2-1/2	63.50	3.13	79.50	2	400	2.76	15.00	381.00	1.80	2.67

▲ = Make To Order (MTO)